



## PRODUCT DESCRIPTION

Dimensions	1288mm x 190mm
Thickness	8mm
Bevels	4
Loc System Classification of use	5G Loc under licence of Välinge Innovation AB Class 23/32 According to European Standard EN13329

	Contains	m <sup>2</sup>	ft <sup>2</sup>	Weight
1 pack	9 planks	2,20 m <sup>2</sup>	23,71 ft <sup>2</sup>	15,7 kg
1 pallet	56 packs	123,34 m <sup>2</sup>	1327,61 ft <sup>2</sup>	891 kg

## COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF) treated with HydroPlus water repelling technology
Backing	Direct laminated paper, impregnated with melamine resin

## TESTED VALUE

Abrasion resistance

## METHOD

EN13329

## TEST RESULTS

AC4 (IP≥4000)

Impact resistance

EN13329

Small ball : ≥ 12 N - Big ball : ≥ 750 mm

Thickness swelling

EN13329

12% (requirement ≤ 18%)

Fire resistance

EN14041

Cfl-S1

Formaldehyde

EN14041

E1

Slipperiness

EN14041

DS

Density

EN323

900 kg/m<sup>3</sup>

Resistance to staining

EN438

5 (groups 1+2); 4 (group 3)

Resistance to cigarette burns

EN438

4

Effect of a furniture leg

EN424

No damage (foot type 0)

Effect of a castor chair

EN425

No change in appearance or damage

Thermal resistance in combination with underlay Excellence Plus

0,08 m<sup>2</sup>K/W – Suitable for floor heating/cooling. Detailed instructions on [www.berryalloc.com](http://www.berryalloc.com)

## CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- DOP : 170-DPLA18-1

## WARRANTY

- Lifetime Residential Warranty
- 5 Years of Commercial Warranty
- Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com)

