



BESKRIVELSE			
Total tykkelse	EN 428	mm	2.00
Vekt	EN 430	g/m ²	3120
Flisstørrelse	EN 427	mm	608 x 608
Antall fliser/pakke	-	-	20
KLASSIFISERING			
Norm	-	-	EN 649
Europaklasse	EN 685		34 - 43
K klasse	-	class	K5
Brannklassifisering	EN 13 501-1	klasse	B _{fl} -s1
Kritisk strålingsperiode	ASTM E648	W/cm ²	class 1
Elektrostatisk oppladning	EN 1815	kV	< 2
TESTVERDIER			
Slitestyrke	EN 660.2	mm ³	≤ 4.0
Slitasjegruppe	EN 649	gruppe	P
Type Binder content	ISO 10581	type	I
Dimensjonsstabilitet	EN 434	%	≤ 0.25
Inntrykksfasthet	EN 433	mm	~ 0.03
Rullende stolhjul (typen W)	EN 425	-	OK
Varmemotstand	EN 12 524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Overflatebehandling	-	-	Evercare™
Kjemikaliebestandighet	EN 423	klasse	OK
CE MARKING			
	EN 14041	-	
		-	