## **Declaration of Performance**



## No. DoP1299-0302 SkamoStructure Board 250

1. Product type:

Calcium Silicate Boards (CS)

2. Constructions product identification:

SkamoStructure Board 250 (Building)

Density 250 kg/m<sup>3</sup>

Intended use of construction product:

Fire protective boar.

Product for internal use designated as type Z<sub>2</sub> in EAD 350142-00-1106

The manufacturer's name and address:

Skamol A/S, DK-7900 Nykøbing Mors, Østergade 58-60

5. The authorized representative's name and address:

DBI Certification A/S, Jernholmen 12, DK-2650 Hvidovre, Notified body 2531

Systems of assessment and verification of constancy of the performance (AVCP):

AVCP-System, according to table 8 declared performance.

EC Certificate of conformity No: 2531-CPR-CXO10003, Fire Class A1, system1, under the regulation (EU) No. 305/2011 European Technical Assessment No. ETA-11/0469, issued by ETA Denmark, European Assessment Document no. EAD 350142-00-1106 Fire protective board, slab and mat products and kits

Notified body tasks, if relevant:

DBI 2531, Third party tasks performed according to appendix V part B under system 1

Declared performance: 8.

| Essential characteristics                               | AVCP<br>System | Performance                     | Harmonised technical specification |
|---|----------------|---------------------------------|------------------------------------|
| Reaction to fire  | 1              | Class A1                        | EAD 350142-00-1106                 |
| Thermal conductivity, λ10-value                         | 3              | 0,066 W/(mxK)                   | EAD 350142-00-1106                 |
| Release of dangerous substances                         | 3              | NPD                             | EAD 350142-00-1106                 |
| Dimensions  | 3              | As stated on the packaging      | EAD 350142-00-1106                 |
| Dimensional stability                                   | 3              | 0.0 %                           | EAD 350142-00-1106                 |
| Compressive strength                                    | 3              | 2800 kPa, CS(10)2000 ≥ 2000 kPa | EAD 350142-00-1106                 |
| Short term water absorption                             | 3              | NPD                             | EAD 350142-00-1106                 |
| Water vapour permeability, (transmission coefficient),µ | 3              | NPD                             | EAD 350142-00-1106                 |

The performance of the construction product referred to in point 1 and 2, are consistent with the declared performance in point 8.

This declaration of performance issued on the sole responsibility of the manufacturer, listed in point 4. Signed for and on behalf of the production by:

100 Jørgen Mikkelsen

R & D Development Manager, Skamol A/S

Nykøbing Mors 14-08-2018 rev0



Østergade 58-60, 7900 Nykøbing Mors, Denmark

Tel.: +45 97 72 15 33

www.skamol.com

